物質安全資料表

Material Safety Data Sheet

1 製造商或供應商資料 Manufacturer Information

| 公司資料 | 聯景金屬材料(惠州)有限公司 | | |
|-----------------------------|---|-------------|--------------|
| Company Name | LIAN JING METAL MATERIAL(HUI ZHOU)CO;LTD | | |
| 地址 Address | 廣東省惠州仲恺高新區陳江街道辦事處澄海村工業區 CHENGHAI AREA, CHENJING TOWN, HUIZHOU CITY, GUANGDONG | | |
| 聯絡人 | 陳陞 | | |
| Person in Charge | David | | |
| 緊急連絡電話 Emergency Phone # | 0752-3178082 | 傳真 Fax # | 0752-3178083 |
| 產品種類 | 無鉛錫條 | | |
| Product Type | Lead-Free Solder Bar | | |
| 名稱 Common Name | LJ9635B | | |

2 危害物質分類 Hazardous Ingredients

| 危害性成分 Hazardous Components 名稱 Common Name 比率 Weight % | | 化學文摘社 | 時量平均 容許溶度 | 許濃度 計 | 最高容 | 測試動物 吸收途徑 LD 50 (mg/Kg) | 測試動 物吸收 途徑 LC 50 | | |
|---|--------|-------|------------------|-----------|----------------|----------------------------------|---------------------------|-----|-----|
| | | | 登記號碼 TWA (mg/m³) | | 許濃度 CEILING | | | | |
| 錫 | Tin | Sn | Bal. | 7440-31-5 | 2 | 4 | N/A | N/A | N/A |
| 銀 | Silver | Ag | 3 | 7440-22-4 | 0.01 | 0.03 | N/A | N/A | N/A |
| 4司(| Copper | Cu | 0.5 | 7440-50-8 | 0.2 | N/A | N/A | N/A | N/A |

3 危害物質定義 Hazards Identification

| 物質狀態及外觀 | 固體 |
|--------------------------------|---|
| Physical State and Appearance | Solid. |
| 緊急情況概要 | 警告!WARNING! |
| Emergency Overview | 避免接觸到眼睛. 嚴禁吞食. 避免吸入粉塵. 避免過長或是反覆的 |
| | 皮膚接觸. 保持容器緊閉. 當空流通良好時使, 並於使用後徹底洗淨. |
| | Avoid contact with eyes. DO NOT ingest. Do not breathe dust. Avoid |
| | prolonged or repeated contact with skin. Keep container closed. Use olny |
| | with adequate ventilation. Wash thoroughly after handling. |
| 潛入人體的途徑 Routes of Entry | 吸入. 吞食. Inhalation. Ingestion. |
| 潛在的急性健康影響 眼睛 | 青如果發生眼睛接觸(刺激物,腐蝕物),這產品可能是有害的. |
| Potential Acute Health Effects | 眼睛接觸可能導致角膜受損或是失明. |
| Eye | es This product may be hazardous in case of eye contact (irritant,corrosive). |
| | Eye contact can result in corneal damage or blindness. |

| 皮膚 | 如果發生皮膚接觸(刺激物,致敏物質),這產品可能是有害的. |
|----------------------------------|---|
| | 對皮膚爲非腐蝕性,非滲透性.皮膚發炎的症狀有發癢,鱗癬,發紅 |
| | 或是偶爾起水泡. |
| Skin | This product may be hazardous in case of skin contact (irritant, sensitizer). |
| | Non-corrosive for skin.Non-permeator by skin. Skin inflammation is |
| | characterized by itching, scaling, reddening, or, occasionally, blistering. |
| 吸入 | 如果發生吸入的情況,這個產品所產生的煙塵可能是有害的. |
| Inhalation | Fumes and/or dusts produced by this product may be hazardous in case of |
| | inhalation. |
| 吞食 | 如果發生吞食的情況,這個產品所產生的煙塵可能是有害的. |
| Ingestion | Fumes and/or dusts produced by this product may be hazardous in case of |
| | ingestion. |
| 潛在的慢性病影響 | 如果發生吞食或吸入的情況,這個產品所產生的煙塵可能是有害的. |
| Potential Chronic Health Effects | 如果發生皮膚接觸(刺激物,致敏物質),或是眼睛接觸(刺激物) |
| | 可能是有害的. 對皮膚非腐蝕性, 非滲透性. |
| | Fumes and/or dusts produced by this product may be hazardous in case of |
| | ingestion, of inhalation. This product may be hazardous in case of skin |
| | contact(irritant,sensitizer),of eye contact(irritant).Non-corrosive for |
| | skin.Non-permeator by skin. |
| 曝露過度所造成的重大醫學疾病 | 對於毒性物質反覆的曝露可能累積毒物在一個或多個人體器官, |
| Medical Conditions Aggravated by | 造成健康的惡化. |
| Overexposure | Repeated exposure to toxic material may produce general deterioration |
| | of health by an accumulation in one or many human organs. |
| 曝露過度/症狀/徵狀 | 無法提供. |
| Overexposure/ Signs/ Symptoms | Not available. |
| 詳見毒物資料(第11點說明) | See Toxicological Information (Section 11) |

4 急救措施 First Aid Measures

| 眼睛接觸 | 檢查並移除任何隱形眼鏡. 如果發生任何接觸, 馬上用大量清水 | |
|------------------------|---|--|
| Eye Contact | 沖洗眼睛至少15分鐘. 立即就醫. | |
| | Check for and remove any contact lenses. In case of contact, immediately | |
| | flush eyes with plenty of water for at least 15 minutes. Get medical attention. | |
| 皮膚接觸 | 假如發生接觸,在移除受污染的衣物和鞋子時,馬上用大量清水沖 | |
| Skin Contact | 洗皮膚至少15分鐘. 用潤膚劑覆蓋發炎的皮膚. 衣服及鞋子如要再 | |
| | 使用時,應徹底清洗乾淨.馬上就醫. | |
| | In case of contact, immediately flush skin with plenty of water for at least | |
| | 15 minutes while removing contaminated clothing and shoes. Cover the | |
| | irritated skin with an emollient. Wash clothing before reuse. Thoroughly | |
| | clean shoes before reuse.Get medical attention. | |
| 有害物質的皮膚接觸 | 用消毒肥皂清洗,並用抗菌藥膏覆蓋於受污染的皮膚.馬上就醫. | |
| Hazardous Skin Contact | Wash with a disinfectant soap and cover the contaminated skin with an | |
| | anti-bacterial cream.Seek immediate attention. | |

| 吸入 | 如果吸入,移至新鮮空氣處,如果不能呼吸,施予人工呼吸. | |
|----------------------|--|--|
| | | |
| Inhalation | 假如呼吸困難,給予氧氣.馬上就醫. | |
| | If inhaled,remove to fresh air.If not breathing,give artificial respiration.If | |
| | breathing is difficult, give oxygen. Give medical attention immediately. | |
| 有害物質的吸入 | 無法提供. | |
| Hazardous Inhalation | Not available. | |
| 吞食 | 假如吞食,不可催吐,除非經過醫療人員指導.千萬不可給意識不 | |
| Ingestion | 清者吞食任何物品. 鬆開緊貼的衣物, 如衣領, 領帶,皮帶或腰帶等. | |
| | 馬上就醫. | |
| | If swallowed,do not induce vomiting unless directed to do so by medical | |
| | personnel.Never give anything by mouth to an unconscious person. | |
| | Loosen tight clothing such as a collar, tie, belt or waistband. Get medical | |
| | attention immediately. | |
| 有害物質的吞食 | 無法提供. | |
| Hazardous Ingestion | Not available. | |
| 醫師的建議 | 無法提供. | |
| Notes to Physician | Not available. | |

5 火警的措施 Fire Fighting Measures

| 產品的易燃性 | 在高溫時,可能是可燃的 |
|--------------------------------------|---|
| Flammability of the Product | May be combustible at high temperature. |
| 自燃溫度 | 無法提供 |
| Auto-Ignition Temperature | Not available. |
| <i>閃火點</i> | 已知最低的溫度爲攝氏180度(華氏356度).(松香) |
| Flash points | The lowest known value is 180 (356).(Rosin) |
| 易燃的極限 | 無法提供 |
| Flammable Limits | Not available. |
| 產品的燃燒 | 這些產物是碳氧化物(一氧化碳,二氧化碳),氮氧化物 |
| Products of Combustion | (一氧化氮,二氧化氮).一些金屬氧化物. |
| | These products are carbon oxides (CO, CO ₂),nitrogen oxides (NO, |
| | NO ₂).Some metallic oxides. |
| 呈現於各種物質下的火災危害 | 在開放性的火焰火花的情況下是可燃的. 在撞擊, 熱, 氧化物質, |
| Fire Hazards in Presence of | 還原物質,可燃物質,有機物質,金屬,酸,鹼,潮濕的情況下是 |
| Various Substances | 不可燃的. |
| | Combustible in presence of open flames and sparks. Non-flammable in |
| | presence of shocks, of heat, of oxidizing materials, of reducing materials, |
| | of combustible materials, of organic materials, of metals, of acids, of alkalis, of moisture. |
| 呈現於各種物質下的爆炸危害 | 在開放的火焰火花,撞擊下,不會有爆炸的情形發生. |
| Explosion Hazards in Presence | Non-explosive in presence of open flames and sparks, of shocks. |
| of Various Substances | |
| 火警的媒介與指示 | 小火: 使用乾粉滅火器 |
| Fire Fighting Media and Instructions | 大火: 使用水霧或泡沫噴灑. 不要使用水噴射. |

| | SMALL FIRE: Use DRY chemical powder. | |
|--|---|--|
| | LARGE FIRE: Use water spray, fog or foam.DO NOT use water jet. | |
| 防護衣(火) | 確認使用一個經過認可/證明的口罩或是相等物. | |
| Protective Clothing (Fire) | Be sure to use an approved/certified respirator or equivalent. | |
| 火災危害的特殊註解 | 大量金屬是不易燃的. 粉塵及粉末可能是可燃的. | |
| Special Remarks on Fire Hazards | Massive metal is nonflammable. Dust and powders may be flammable. (Tin) | |
| 爆炸危害的特殊註解 | 無法提供 | |
| Special Remarks on Explosion Hazards No available. | | |

6 避免意外的措施 Accidental Release Measures

| 小量的溢出與洩漏 | 使用適當的工具來放置溢出的固體於合宜的廢棄物處理容器中. |
|----------------------|---|
| Small Spill and Leak | 噴灑水於在受污染的表面完成清潔,並且根據地方當局的要求處理. Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the |
| | contaminated surface and dispose of according to local and regional |
| | authority requirements. |
| 大量的溢出和洩漏 | 假如發生產品的溢出或洩漏,我們的資料顯示沒有額外的資訊 |
| Large Spill and Leak | Our data base contains no additional information in case of a spill |
| | and/or a leak of the product. |

7 操作與儲藏 Handling and Storage

| 操作 | 避免與眼睛接觸. 嚴禁吞食. 嚴禁吸入粉塵. 避免過長或 | |
|----------|--|--|
| Handling | 反覆的皮膚接觸. 保持容器緊閉. 在通風良好的情況下操作. | |
| | 使用後徹底洗淨. | |
| | Avoid contact with eyes. DO NOT ingest.DO not breathe dust. Avoid | |
| | prolonged or repeated contact with skin. Keep container closed. Use only | |
| | with adequate ventilation. Wash thoroughly after handing. | |
| 儲藏 | 保持容器緊密關閉. 保持容器於一個涼爽, 通風良好的區域. | |
| Storage | Keep container tightly closed. Keep container in a cool, well-ventilated area. | |

8 曝露的控制,個人的保護措施 Exposure Controls,Personal Protection

| | | 當流通的空氣不足時,請穿戴適當的口罩. |
|----------------------|---------|---|
| | 呼吸 | 防塵口罩. 確認使用經過一個認可/證明的口罩或是相等物. |
| Personal Protection | 身體 Body | 實驗室外套 Lab coat. |
| 個人安全的保護 | 眼睛 Eyes | 護目鏡 Splash goggles. |
| | | exposure to airborne contaminants below the exposure limit. |
| | | If user operations generate dust, fume or mist, use ventilation to keep |
| | | Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. |
| | | 於爆炸界線。 |
| | | 生煙,塵或霧,使用通風良好的設備來維持空氣中污染的爆炸性低 |
| Engineering Controls | | 持空氣中的水平在建議爆炸範圍之下. 假如使用者操作過程產 |
| 工程上的保護 | | 使用圍住製程區域,區域排氣通風良好,或其他工程上的控制來維 |

Respiratory Dust respirator.Be sure to use an approved/certified respirator or equivalent.Wear appropriate respirator when ventilation is inadequate.

手 Hands 手套 Gloves.

腳 Feet 不適用 Not applicable

註解: 建議穿上保護的衣物在特定過程中可能是不足夠的. 使用前麻煩先諮詢專家.

* Note: Suggested protective clothing may not be adequate for a specific process.

Consult a specialist before using.

假如發生大量溢出時的個人安全保護沒有額外的資訊

Personal Protection in Case No additional information.

of a Large Spill

產品名稱 Product Name 曝露極限 Exposure Limits

(1) 錫 Tin TWA:2 (mg/m³)

(2) 銀 Silver TWA: 0.01(mg/m³)

(3) 銅 Copper TWA: 0.2(mg/m³)

諮詢地方當局的專家,可接受的曝露範圍.

Consult local authorities for acceptable exposure limits.

9 化學與物理特性 Physical and Chemical Properties

| 物理狀態與外觀 Physical State and Appearance | 固態Solid. |
|---------------------------------------|--|
| 分子量 Molecular Weight | 不適用 Not applicable. |
| 化學式 Chemical Formula | 不適用 Not applicable. |
| 酸鹼值 pH (1% Soln/ Water) | 不適用 Not applicable. |
| 酸價 Acid Value | 無法提供 Not available. |
| 沸點/凝結點 Boiling/Condensation Point | 無法提供 Not available. |
| 熔點 Melting | 攝氏217~218度 217~218℃ |
| 臨界溫度 Critical Temperature | 無法提供 Not available. |
| 蒸氣壓 Vapor Pressure | 不適用 Not applicable. |
| 蒸氣密度 Vapor Density | 無法提供 Not available. |
| 揮發度 Volatility | 無法提供 Not available. |
| 初味 Odor Threshold | 無法提供 Not available. |
| 氣味 Odor | 松香特有的氣味 Typical rosin. |
| 味覺 Taste | 不適用 Not applicable. |
| 顏色 Color | 深灰色 Dark grey. |
| 比重 Specific Gravity | 7.4 (水=1) 7.4(water=1) |
| 蒸發速度 Evaporation Rate | 無法提供 Not available. |
| 揮發溶劑的有機化合物 VOC | 無法提供 Not available. |
| LogK _{ow} | 這個產品在水中及油中是不溶解的 |
| | The product is insoluble in water and oil. |
| 電解度 Ionicity (in water) | 非離子 Non-ionic. |
| 分散特性 Dispersion Properties | 在冷水, 熱水, n-辛醇, 丙酮中無法被分離. |
| | Is not dispersed in cold water, hot water, n-octanol, acetone. |

| 溶解性Solubility | 在甲醇,乙醚微溶. 在冷水,熱水,丙酮中不溶. |
|------------------------------------|---|
| | Very slightly soluble in methanol, diethyl ether. |
| | Insoluble in cold water, hot water, n-octanol, acetone. |
| 物理化學的註解 Physical Chemical Comments | 無法提供 Not available. |

10 穩定性與反應特性 Stability and Reactivity

| 穩定性與反應特性 | | 這個產品是穩定的. |
|----------------------------|---------------------------------------|--|
| Stability and Reactivity | | The product is stable. |
| 不穩定的狀態 | | 正常情況下是穩定的. 超過熔點, 會散發出有毒的錫氧化物(錫). |
| Conditions of Instability | | Stable in normal conditions. Over melting point, will emit toxic tin oxides.(Tin |
| 各種物質的不相容性 | | 對酸有強烈的反應.對氧化劑,溼度有輕微的反應. |
| Incompatibility with | | Highly reactive with acids. Slightly reactive with oxidizing agents, moisture. |
| Various Substances | | |
| 危害的分解產品 | | 無法提供 |
| Hazardous Decomposition Pr | roducts | Not available. |
| 危害的聚合作用 | | 不會發生 |
| Hazardous Polymerization | | Will not occur. |
| 腐蝕性 | 對玻璃,鈴 | 岡, 鋁, 鋅, 不鏽鋼(304), 不鏽鋼(316). |
| Corrosivity | Non-corre | osive in presence of glass, of steel, of aluminum, of zinc, of stainless |
| | steel(304) | of stainless steel(316). |
| 對腐蝕性的特殊註解 | 在錫膏中的有機助焊劑主要任務是清潔(移除及預防氧化)銲錫表面. | |
| Special Remarks on | The organ | nic medium in a paste has task of cleaning (removing and preventing |
| Corrosivity | oxydation)the surface for soldering. | |

11 毒物資料 Toxicological Information

| 對人類的毒性及慢性影響 | 這個產品所產生的煙及塵,假如發生吞食或是吸入時,可能會造成 | |
|-------------------|---|--|
| Toxic and Chronic | 危害. 假如發生皮膚接觸 (刺激物,致敏物質),眼睛接觸 (刺激物) | |
| Effects on Humans | 對皮膚爲非腐蝕性,也不會有滲透性. | |
| | Fumes and/or dusts produced by this product may be hazardous in case of | |
| | ingestion, of inhalation. This product may be hazardous in case of skin contact | |
| | (irritant, sensitizer), of eye contact (irritant). Non-corrosive for skin. Non- | |
| | permeator by skin. | |
| | 誘導突變的影響: 無法提供 | |
| | MUTAGENIC EFFECTS: Not available. | |
| | 畸形的影響: 無法提供 | |
| | TERATOGENIC EFFECTS: Not available. | |
| | 毒性的發展: 沒有毒性 | |
| | DEVELOPMENTAL TOXICITY:Not toxic. | |
| | 這產品對肺臟,黏膜,上呼吸道,皮膚,眼睛,眼球,角膜,甲狀腺可能有毒性. | |
| | 反覆或是過長的曝露於這種物質下可能造成特定器官的損害. 反覆的曝露 | |
| | 於毒性的物質下可能累積毒物在一個或多個人體器官,造成健康的惡化. | |

| | The product may be toxic to lungs, mucous membranes, upper respiratory tract, |
|---------------------------|--|
| | skin,eye,lens or cornea,thyroid. Repeated or prolonged exposure to the substance |
| | can produce target organs damage.Repeated exposure to toxic material may produce |
| | general deterioration of health by an accumulation in one or many human organs. |
| 對動物的毒物性 | 關於動物的毒性,在我們的資料中沒有特殊的報告. |
| Toxicity to Animals | No specific information is available in our data base regarding the toxicity to animals. |
| 對人類慢性影響的 | 過長或反覆的曝露於氧化錫的煙霧中可能導致肺塵病(錫). |
| 特殊註解 | Prolonged and repeated exposure to tin oxyde fumes may result in pneumoconiosis |
| Special Remarks on | (stannosis). |
| Chronic Effects on Humans | |
| 對人類其他毒物影響 | 如果在高溫時吸入煙或塵可能會導致氣喘反應. |
| 的特殊註解 | 融熔金屬可能造成嚴重的燒傷. |
| Special Remarks on | Inhalation of smoke and fumes, at hight temperatures, may cause an asthmatic |
| Other Toxic Effects | reaction in some individuals. |
| on Humans | MOLTEN METAL can cause sever BURNS! |
| 毒性對動物的特殊註解 | 沒有額外的註解(錫) |
| Special Remarks on | No additional remark. (Tin) |
| Toxicity to Animals | |

12 生態資料 Ecological Information

| 環境毒性 Ecotoxicity | 無法提供 Not available. |
|-----------------------------|---|
| 生化需氧量 BOD5 and COD | 無法提供 Not available. |
| 生物分解性 Biodegradable/ OECD | 無法提供 Not available. |
| 流動性 Mobility | 無法提供 Not available. |
| 產品的生物分解的毒性 | 產品品質的下降比產品本身較具有毒性. |
| Toxicity of the Products of | The products of degradation are less toxic than the |
| Biodegradation | product itself. |
| 對產品生物分解的特殊註解 | 無法提供. |
| Special Remarks on the | Not available. |
| Products of Biodegradation | |

13 廢棄物處置辦法 Disposal Considerations

| 廢棄物資訊 | 廢棄物的處理需要符合當地政府的控制規定. | |
|--|---|--|
| Waste Information | Waste must be disposed of in accordance with local environmental control regulations. | |
| 廢棄物流向 | 無法提供 | |
| Waste Stream | Not available. | |
| 諮詢當地或所屬地區專家Consult your local or regional authorities. | | |

14 運送資料 Transport Information

| 運輸部分類 | 不是一個DOT控制的物料 (美國) |
|----------------------------------|--|
| DOT Classification | Not a DOT controlled material (United States). |
| 運輸特別條款 | 不適用 |
| Special Provisions for Transport | Not applicable. |

| IMO/IMDG 分類 | 不在IMDG的規定下 |
|---------------------------|-------------------------------------|
| IMO/ IMDG Classification | Not controlled under IMDG |
| 海運的污染 Marine Pollutant | 無法提供 Not available. |
| ADR/RID 分類 | 不在ADR的規定之下(歐洲) |
| ADR/ RID Classification | Not controlled under ADR (Europe) |
| 國際民航組織/國際空運協會分類 | 不在國際空運協會規定下 |
| ICAO/ IATA Classification | Not controlled under IATA |

15 管理資訊 Regulatory Information

| HCS 分類 | 等級: 刺激物質 Class: Irritating substance. |
|---------------------------|---|
| HCS Classification | 等級: 敏感性物質 Class: Sensitizing substance. |
| | 等級: 特定器官影響 Class: Target organ effects. |
| International Regulations | <i>即際性管理</i> |
| EINECS | Not available. |
| DSCL (EEC) | 21/22-接觸到皮膚或是吞下的可能是有害的 |
| | 36/38- 刺激眼睛及皮膚 |
| | 42-43- 經吞食或是皮膚接觸能導致過敏作用. |
| | 21/22-Harmful in contact with skin and if swallowed. |
| | 36/38-Irritating to eyes and skin. |
| | 42/43-May cause sensitization by inhalation and skin contact. |
| 國際名冊International Lists | 澳大利亞Australia(NICNAS): 所有成分All components. |
| | 韓國Korea(TCCL): 所有成分All components. |
| | 菲律賓 Philippines(RA6969): 所有成分All components. |

16 其他資料 Other Information

| 聯景金屬材料 | | ∤(惠州)有限公司 |
|----------------|---|--|
| 製表單位 | LIAN JING METAL MATERIAL (HUI ZHOU) CO;LTD 地址:惠州仲恺高新區陳江街道辦事處澄海村工業區 | |
| Company | | |
| | Add:No.CHEN | NGHAI AREA, CHENJING TOWN, HUIZHOU CITY, GUANGDONG |
| 製表人 | 姓名:陳陞 | |
| Person in Char | rge | Name:David |
| 緊急連絡電話 | <u>.</u> | 0752-3178082 |
| Emergency Ph | | 0732-3176062 |
| 傳真 FAX | | 0752-3178083 |